


OVERHEAD LIFTING CHAIN



 WARNING
To prevent the possibility of serious bodily harm: DO NOT EXCEED the working load limits of chain or components DO NOT USE if the chain or components are visibly distorted or worn


Over Head Lifting Chain – Grade 80 - ID markings on select links

Trade Size	WLL 4:1 lbs	Material Diameter	Inside Length	Inside Width	Feet Per Drum	Lbs per 100 Ft	Price Per ft	Part Number
9/32"	3,500	7 mm	21 mm	9 – 10.5 mm	800	70	5.36	28-7MM80LB
5/16"	4,500	8 mm	24 mm	10 – 12 mm	550	92	6.23	28-8MM80LB
3/8"	7,100	10 mm	30 mm	12.5 – 15 mm	400	142	8.26	6-3/8" G80
1/2"	12,000	13 mm	39 mm	16.3 – 20 mm	200	244	13.48	6-1/2" G80
5/8"	18,100	16 mm	48 mm	20 – 24 mm	164	356	22.20	6-5/8" G80
3/4"	28,300	20 mm	60 mm	25 – 30 mm	164	562	28.96	6-3/4" G80
7/8"	34,200	22 mm	66 mm	28 – 33 mm	164	720	57.14	6-7/8" G80
1"	47,700	26 mm	78 mm	35 – 39 mm	110	990	75.50	6-1" G80
1-1/4"	72,300	32 mm	96 mm	40 – 42 mm	82	1580	151.87	6-1-1/4" G80

Campbell®



- Specifically recommended for overhead lifting
- 25% stronger than System 8
- Enables you to perform same lifts with lighter weight chain
- System 10 chain should not be plated or galvanized
- Hallmarking: C10 and traceability code
- Standard material: Alloy steel, heat treated
- Standard finish: Bright (BRT)
- Proof tested
- Order unit is "Feet"

 WARNING
To prevent the possibility of serious bodily harm: DO NOT EXCEED the working load limits of chain or components DO NOT USE if the chain or components are visibly distorted or worn

Over Head Lifting Chain – Grade 100

Trade Size	WLL 4:1 lbs	Material Diameter	Inside Length	Inside Width	Feet Per Drum	Lbs per 100 Ft	Price Per ft	Part Number
9/32"	4,300	0.29"	0.86"	0.41"	500	70	7.81	35-9/32" G100
3/8"	8,800	0.40"	1.22"	0.55"	500	142	9.58	35-3/8" G100
1/2"	15,000	0.52"	1.57"	0.75"	300	244	16.27	35-1/2" G100
5/8"	22,600	0.64"	1.93"	0.87"	200	356	23.22	35-5/8" G100
3/4"	35,300	0.80"	2.42"	1.09"	100	598	39.28	35-3/4" G100

 WARNING
NEVER EXCEED PUBLISHED WORKING LOAD LIMIT